

# VINYL SHEET FLOORING

ROBUST  
AND RELIABLE

DISTRIBUTORS OF

**BEAU  
FLOR®**  
we decorate your floor

**RESPONSIVE**  
We listen. We're responsive.

DISTRIBUTED BY







PRODUCT APPLICATIONS

- Housing
- Offices
- Education
- Hospitality
- Public Space
- Retail spaces

SIZE (WIDTH)

2m

LENGTH

20 LINEAL  
METRES

THICKNESS

2.5mm

WEAR LAYER

0.7mm

# Ambient

## HEAVY DUTY VINYL SHEET

HEAVY DUTY VINYL

With a tough 0.7mm wear layer, Ambient is perfect for large installations, heavy domestic, commercial and light industrial use.

Our Ambient vinyl sheet range has decors that emulate the look of timber with the durability of vinyl. Ambient offers a stunning balance between sophistication and bold new styles blending seamlessly to provide a chic and stylish palette.

Available in a myriad of hues and stipple designs, this range is not only aesthetically pleasing but able to withstand intense traffic with its 0.7mm wear layer and 2.5mm thickness.

Special dirt resistant wear layer

100% Recyclable product

10 year commercial warranty

20 year residential warranty

Class Rating 23, 33, 42

Easy to maintain

Waffle back emboss - providing better adhesion

Faster installation

Phthalate free

VOC Compliant

FEATURES AND BENEFITS



HAVANNA OAK  
669D



ANTIQUE OAK  
026M



HONEY OAK  
636M



GOLDEN OAK  
696L



HAVANNA OAK  
991M



EDITH  
777D



EDITH  
999D



EDITH  
997M





PRODUCT APPLICATIONS

- Safety and Transport
- Marine
- Wet Areas
- Fitness Centres
- Healthcare
- Laboratories
- Education

SIZE (WIDTH)

2m

LENGTH

20 LINEAL  
METRES

THICKNESS

2mm

WEAR LAYER

1mm

# Canopus Plus

## SAFETY VINYL SHEET

SAFETY VINYL

Robust and reliable, Canopus Plus® is the safety floor of choice where tough performance and durability are most important.

The Canopus Plus® range of safety vinyl sheet flooring combines high performance with attractive designs that will transform any commercial space.

With its 1mm wear layer Canopus Plus® is also widely used for heavy foot traffic areas.

Sureclean™ surface treatment for a dirt resistant surface

Low smoke density

10 year commercial warranty

Antifungal and antibacterial

Decorative effect achieved with carbide particles

Better dimensional stability - with a reinforced glass fibre grid

Class rating 34, 43

Easy to maintain


Chemical resistant

VOC Compliant

No wax or polish required

Phthalate Free

FEATURES AND BENEFITS




**SMOKE**  
4419-322-4




**MIDNIGHT**  
4419-329-4



**GREY TOWN**  
4419-504-4



**PEWTER**  
4419-324-4



**SAND**  
4419-502-4

# Ambient

## HEAVY DUTY VINYL SHEET



SIZE (WIDTH)	LENGTH	THICKNESS	WEAR LAYER
2m	20 LINEAL METRES	2.5mm	0.7mm

Characteristics	Standards	Ambient
Phthalate Free		Yes
Dimensional stability	EN ISO 23999 (EN 434)	≤ 0.40%
Curling	EN ISO 23999	≤ 8mm
Light stability	EN ISO 105 B02	≥ 6°
Residual indentation	EN ISO 24343-1 (EN 433)	≤ 0.10mm
Impact sound improvement	EN ISO 717/2	Δ Lw 13dB
Dynamic coefficient of friction	EN 13893	> 0.6
Slip resistance (ramp test with oil)	DIN 51130	DS
Reaction to fire Report number VNLF 031380.4	EN 13501-1	Bfl-s1 class
Underfloor heating	EN 12667	Suitable
Thermal resistance	ISO 8302	0.025 m²K/w
Thermal conductivity	EN 12524	0.10 W/(m.K)
Chemical resistance/effect of stains	ISO 26987 (EN 423)	Resistant
Static Electrical Propensity	EN 1815	< 2kV
Delamination test (peel resistance)	EN ISO 24345	≥ 50N/50mm
Furniture leg resistance	ISO 16581 (EN 424)	No damage
Castor chair resistance	EN ISO 4918	Suitable (type wheel H)
General performance		23: Heavy duty residential 33: Heavy duty commercial 42: Light industrial use
Sheet size		m (width) 2
		m (length) 20
		m² (surface area) 40

Please note that the data given could be imprecise and liable to modifications of a technical nature at any time. The information in these documents is valid from 01/01/2017 and Beauflor reserve the right to make changes at any moment and without prior notice. Our technology is constantly evolving, so before carrying out any projects we encourage you to contact AFS to maintain our highest level of standards.



100% phthalate free  
\*for all products produced  
from May 2017 onwards



RESIDENTIAL COMMERCIAL

AFS Global Services

# Canopus Plus

## SAFETY VINYL SHEET

**RESPONSIVE**  
We listen. We're responsive.

SIZE (WIDTH)	LENGTH	THICKNESS	WEAR LAYER
2m	20 LINEAL METRES	2mm	1mm
Characteristics	Standards	Units	Canopus Plus®
Phthalate Free			Yes
Indoor Air Quality	CA Section 01350 ( $\leq 0.5 \text{ mg / m}^3$ )	Floorscore Certified (SCS - FS - 04547)	Yes
	ISO 16000-6, TVOC after 28 days	$\mu\text{g/m}^3$	< 10 (Fully compliant)
<b>Description</b>			
Type of floor covering	EN 13845   EN 13553	Classification	Safety Vinyl Flooring
General Performance	ISO 10874 - EN 685		34: Very Heavy Commercial. 43: Heavy Light Industrial
Usage / Wear Resistance	BS EN 649	Group	T ( $\leq 2 \text{ mm}^3$ )
Special Treatment			Anti-slip surface with silicon carbide granules. SureClean™
Overall Thickness	ISO 24346 - EN 428	mm	2.00
Weight	ISO 23997 - EN 430	$\text{g/m}^2$	3400
Sheet Size	ISO 24341 - EN 426	m (width)	2
		m (length)	20
		$\text{m}^2$ (surface area)	40
Castor chair test	ISO 4918 - EN 425	Type of use	Continuous
Dimensional stability	ISO 23999 - EN 434	%	$\leq 0.40$
Flexibility	ISO 24344 - EN 435	20mm mandrel	< 20
Seam Strength	ISO 16906	N/50mm	Pass
Residual indentation	ISO 24343 - 1 - EN 433	mm	$\leq 0.10$
	ASTM F970	psi	800
Colour fastness to light	EN ISO 105 - B02	Degrees	$\geq 6$
	ASTM F1515	$\Delta E \leq 800$ after 300 hours (colour change)	Pass
Static electrical propensity	EN 1815	kV	< 2.0
Thermal resistance	EN 12667	$\text{m}^2 \text{ k/W}$	Approx $0.01 \text{ m}^2 \text{ k/W}$ (suitable at 27°C)
Heat Stability	ASTM 1514	$\Delta E \leq 0.80$ (colour change)	Pass
Reaction to fire	EN ISO 9239-1	$\text{kW/m}^2$	$\geq 8$
	EN ISO 11925-2		Pass
	EN 13501-1 : 2007+A1	Class	Bfl - S1
	ASTM E 648	Type	1
Smoke density	ASTM E 662	Dm	< 450
Stain & chemical resistance	ISO 26987 - EN 423	Index	0 (Excellent resistance)
Maritime usage	IMO RES A 653 (16)		Annex 1 Part 2 (Smoke & Toxicity)
	IMO MSC 61 (67)		Part 5 ( Spread of Flame) and Annexure 2
	Marine Equipment Directive		1121



SCS Global Services





**Australian Flooring Supplies**

68 Prosperity Way  
Dandenong South VIC 3175

**P** 1300 737 155

**E** [salesaust@qep.com](mailto:salesaust@qep.com)

**W** [qep-aust.com.au/afs](http://qep-aust.com.au/afs)

DISTRIBUTED BY

